



AN9616H(F)/ 9613H(F)

Ground Bond Testers

Main Features:

- ◆ Compliant with IEC60335 , IEC60601 , JIG984-2004 standard requirements
- ◆ 60A, AC constant output, 50Hz/60Hz frequency output
- ◆ LCD display model available
- ◆ Upper and Lower limit set, auto test, test line clear to zero
- ◆ Intelligent judgment, voice and light alarm, large font display
- ◆ 8-group and 8-step test condition memory
- ◆ Advanced PWM control and DSP technical
- ◆ High accuracy, High efficiency, Large capacity, small volume.

Model		AN9616H(F)	AN9613H(F)	
AC Output	Current	3.0~60.0A	AC 3.0~30.0A	
	Voltage	AC 10V MAX		
	Frequency	50Hz/60Hz ,optional ± 100ppM		
Parameter Setting	Current	Setting Range	AC 3.0~60.0A	
		Resolution	0.1A	
	Resistance	Upper Limit Setting	1mΩ ~1000mΩ	
		Lower Limit Setting	1mΩ ~1000mΩ	
		Resolution	1mΩ	
		Accuracy	± (2% of upper/lower setting+2mΩ)	
	Voltage	Upper Limit Setting	0.00~10.00V	
		Lower Limit Setting	0.00~10.00V	
		Resolution	0.01V	
		Accuracy	± (1%of upper/lower setting+0.02V)	
Test Time	Range	0.5 - 999.9s (0=continuous)		
	Resolution	0.1s		
Measuring Functions	Current	Current Range	AC 3.0~62.0A	
		Current Resolution	0.1A	
		Current Accuracy	± (1% of reading+4 counts)	
	Resistance	Resistance Range	1mΩ ~1000mΩ	
		Resistance Resolution	1mΩ	
		Resistance Accuracy	± (2% of reading+2 counts)	
		Auto Reset to Zero Range	0mΩ ~100mΩ , auto/manual	
	Voltage	Voltage Range	AC 0.00~10.00V	
		Voltage Resolution	0.01V	
		Voltage Accuracy	± (1% of reading+2 counts)	
	Auto Reset to Zero Voltage	0.00~1.00V , auto/manual		
	Display	LCDdisplay		
	Measure Mode	4-lines		
	Interface	RS232(RS485 optional), Printer Start, Stop, Select memory setting 1-8 input, Pass, Fail, Testing, Error output		
	Dimension W × H × D (mm)	400 × 156 × 475		